

# Kitchen door care & maintenance

## Vinyl kitchen doors

- For product cleaning ONLY use a 5% soap, 95% water (liquid soap) solution, wiping with a damp (not wet) cloth, finally drying with a soft clean cloth. Dust with a soft cloth only.
- DO NOT USE wax-furniture polish, abrasive or aggressive cleaners, bleach or other hypochlorate (chlorine) based cleaners, multipurpose-cleaners, dilutes, acetone, alcohol, solvent or similar products on the door as this will damage the surface.
- Cooking splashes should be wiped up immediately using a damp cloth.
- If the doors are supplied with a protective film on the face they must not be directly exposed to sunlight. It is recommended the film is removed as soon as possible.
- Newly plastered rooms should be left to environmentally stabilise before storage and installation of doors.

## Foil

- For product cleaning ONLY use a 5% soap, 95% water (liquid soap) solution, wiping with a damp (not wet) cloth, finally drying with a soft clean cloth. Dust with a soft cloth only.
- DO NOT USE wax-furniture polish, abrasive or aggressive cleaners, bleach or other hypochlorate (chlorine) based cleaners, multipurpose-cleaners, dilutes, acetone, alcohol, solvent or similar products on the door as this will damage the surface.
- Cooking splashes should be wiped up immediately using a damp cloth.
- Newly plastered rooms should be left to environmentally stabilise before storage and installation of doors.

## Timber

- DO NOT USE abrasive or aggressive cleaners, bleach or other hypochlorate (chlorine) based cleaners, multipurpose-cleaners, dilutes, acetone, alcohol, solvent or similar products on the door as this will damage the surface.
- DO NOT USE abrasive or aggressive cleaners, bleach or other hypochlorate (chlorine) based cleaners, multipurpose-cleaners, dilutes, acetone, alcohol, solvent or similar products on the door as this will damage the surface.
- It is advisable to use a damp (not wet) cloth to remove fingerprints and marks, followed at once with a clean and dry soft cloth. Cooking splashes should be wiped up immediately using a damp cloth.
- Newly plastered rooms should be left to environmentally stabilise before storage and installation of doors.

- Please note, care of timber doors that are unfinished/sanded will depend on the type of finish applied, eg paint, stain, wax etc., . The kitchen supplier should advise the care guidance for your choice of surfacing finish

## Stainless Steel

- For product cleaning ONLY use a 5% soap, 95% water (liquid soap) solution, wiping with a damp (not wet) cloth, finally drying with a soft clean cloth, or alternatively clean the surface with a stainless steel cleaner or E-cloth (available from your kitchen retailer). Dust with a soft cloth only.
- DO NOT USE wax-furniture polish, abrasive or aggressive cleaners, bleach or other hypo chlorate (chlorine) based cleaners, multipurpose-cleaners, dilutes, acetone, alcohol, solvent or similar products on the door as this will damage the surface.
- Cooking splashes should be wiped up immediately using a damp cloth.
- A light coat of baby oil can be used to enhance the appearance of the door if required.
- Newly plastered rooms should be left to environmentally stabilise before storage and installation of doors.